



FINAL CONSTRUCTION PLANS

CENTER GROVE HIGH SCHOOL

BLACK BOX THEATER



BENCHMARK INFORMATION	
BM #1	ORIGINATING BENCHMARK
DESIGNATION - X 13	
PID - K4000	
STATE/COUNTY - IN/MORGAN	
USGS QUAD - MOORESVILLE EAST (1980)	
VERT ORDER - FIRST CLASS II	
DESCRIBED BY COAST AND GEODETIC SURVEY 1946	
1.2 MI N FROM WAVERLY	
IN JOHNSON COUNTY, 1.2 MILES NORTH ALONG STATE HIGHWAY 37 FROM THE INTERSECTION OF STATE HIGHWAY 144 AT WAVERLY, MORGAN COUNTY, 125 YARDS NORTH OF THE MORGAN-JOHNSON COUNTY LINE, 26 FEET WEST OF THE CENTERLINE OF THE HIGHWAY, IN LINE WITH THE WEST RIGHT-OF-WAY FENCE, 1.5 FEET SOUTH OF A WHITE WOODEN WITNESS POST, AND ABOUT 2 FEET HIGHER THAN THE HIGHWAY. A STANDARD DISK, STAMPED 686.370 X 13 1930 AND SET IN THE TOP OF A CONCRETE POST PROJECTING 7 INCHES ABOVE GROUND.	
RECOVERY NOTE BY IN DEPT OF NAT RES 1985	
NEW DESC- AT THE INTERSECTION OF NEW STATE ROAD 144 AND OLD STATE ROAD 37, IN THE SOUTHWEST QUARTER OF THE INTERSECTION, WITNESS POST IS GONE RIGHT-OF-WAY FENCE IS GONE, ALL OTHER INFORMATION APPEARS TO BE CORRECT.	
ELEV. = 685.94 (NAVD 88)	
TBM #423	
"OUT BOX" ON NORTH SIDE OF FARTHEST WEST LIGHT POLE BASE ON SOUTH SIDE OF ROAD EAST OF SITE.	
ELEV. = 749.32	



LOCATION MAP
NO SCALE

OWNER/DEVELOPER
CENTER GROVE COMMUNITY SCHOOL CORPORATION
3653 WEST WHITELAND ROAD
PHONE: (317) 881-0515
CONTACT: DARRELL THOMPSON
EMAIL: thompsonjrd@centergrove.k12.in.us

PLANNING ENGINEER
JOHNSON COUNTY PLANNING & ZONING
86 WEST COURT STREET
FRANKLIN, IN 46131
PHONE: (317) 346-4350
CONTACT: RICHARD HOOVER
EMAIL: rhoover@co.johnson.in.us

ENGINEER
CROSSROAD ENGINEERS, PC
115 N 17th AVENUE
BEECH GROVE, IN 46107
PHONE: (317) 780-1555
CONTACT: GREGORY J. ILKO
EMAIL: gilko@crossroadengineers.com

COUNTY SURVEYOR
JOHNSON COUNTY
SURVEYOR'S OFFICE
86 WEST COURT STREET
FRANKLIN, IN 46131
PHONE: (317) 346-4385
CONTACT: GREGG CANTWELL
EMAIL: gcantwell@co.johnson.in.us

DIRECTOR
JOHNSON COUNTY PLANNING & ZONING
86 WEST COURT STREET
FRANKLIN, IN 46131
PHONE: (317) 346-4350
CONTACT: MICHELE HANSARD
EMAIL: mhansard@co.johnson.in.us

TOTAL DISTURBED AREA
PROPOSED IMPROVEMENTS: 0.331 acres

PLAN INDEX	
SHEET #	SUBJECT
100	TITLE SHEET
200	TOPOGRAPHIC SURVEY & DEMOLITION PLAN
300	SITE DIMENSION PLAN
301	CONCRETE TERRACE DETAILS
400	UTILITY PLAN
401	STORM PLAN & PROFILE
500	GRADING PLAN
600	EROSION CONTROL PLAN
601	EROSION CONTROL NOTES
700-701	MISCELLANEOUS DETAILS
800	SPECIFICATIONS

FLOODPLAIN INFORMATION
BY GRAPHIC PLOTTING ONLY, THIS TRACT OF LAND DESCRIBED HEREON LIES WITHIN ZONE "X" (AREAS OUTSIDE THE 500-YEAR FLOODPLAIN) AND IS NOT IN A SPECIAL FLOOD HAZARD AREA AS PLOTTED ON THE FEDERAL EMERGENCY MANAGEMENT AGENCY FLOOD INSURANCE RATE MAP FOR JOHNSON COUNTY, INDIANA, COMMUNITY PANEL NO. 18081C0105D, WHICH BEARS AN EFFECTIVE DATE OF 08/02/2007.

LEGAL DESCRIPTION
BOOK 98, PAGE 451 PART OF THE WEST HALF OF THE NORTHWEST QUARTER OF SECTION FIFTEEN (15), TOWNSHIP THIRTEEN (13) NORTH, RANGE THREE (3) EAST OF THE SECOND PRINCIPAL MERIDIAN, DESCRIBED AS FOLLOWS: BEGINNING AT THE NORTHWEST CORNER OF SAID HALF QUARTER SECTION; THENCE SOUTH ON THE WEST LINE THEREOF, TWENTY-FIVE (25) RODS; THENCE EAST AND PARALLEL WITH THE NORTH LINE OF SAID HALF QUARTER SECTION, TWENTY-SIX (26) RODS AND TWENTY-FOUR (24) LINKS; THENCE SOUTH AND PARALLEL TO THE WEST LINE OF SAID HALF QUARTER SECTION, THIRTY-SEVEN (37) RODS AND TWENTY (20) LINKS; THENCE EAST AND PARALLEL WITH THE NORTH LINE OF SAID HALF QUARTER SECTION, FIFTY-FIVE (55) RODS AND ONE (1) LINK, MORE OR LESS, TO THE EAST LINE OF SAID HALF QUARTER SECTION; THENCE NORTH, SIXTY-TWO (62) RODS AND TWENTY (20) LINKS TO THE NORTHEAST CORNER THEREOF; THENCE WEST, EIGHTY (80) RODS, MORE OR LESS, TO THE PLACE OF BEGINNING, CONTAINING TWENTY-FIVE (25) ACRES, MORE OR LESS.

UTILITIES		
Note: Listed below are the Indiana Underground Plant Protection Services Contacts; Others not listed may exist.		
SEWER GREENWOOD SANITATION 367 S. WASHINGTON ST. GREENWOOD, IN 46143 PHONE: (317) 888-1254 CONTACT: KEITH MEIER	WATER BARGERSVILLE WATER 24 N. MAIN STREET BARGERSVILLE, IN 46106 PHONE: (317) 422-3170 CONTACT: KEVIN KILLINGER	CABLE COMCAST 1600 W. VERNAL PKE BLOOMINGTON, IN 47404 PHONE: (812) 360-3090 CONTACT: STEVE MCARTOR
FIBER ZAYO 9209 CASTLE GATE DRIVE INDIANAPOLIS, IN 46256 PHONE: (765) 341-1199 CONTACT: WAYLON HIGGINS	TELEPHONE AT&T 240 N. MERIDIAN STREET INDIANAPOLIS, IN 46204 PHONE: (317) 265-3050 CONTACT: MATT SPINDLER	ELECTRIC JOHNSON COUNTY REMC 750 INTERNATIONAL DRIVE FRANKLIN, IN 47131 PHONE: (317) 738-7622 CONTACT: DOUG STAHL
METRONET 3701 COMMUNICATIONS WAY EVANSVILLE, IN 47715 PHONE: (812) 213-1050 CONTACT: LORI KEMPER	FIRE DEPARTMENT BARGERSVILLE FIRE DEPARTMENT 3991 N. ST. RD. 135 BARGERSVILLE, IN 46106 PHONE: (317) 422-5187 CONTACT: KEVIN KILLINGER	GAS CENTERPOINT ENERGY 1800 W. 26th STREET MUNCIE, IN 47302 PHONE: (765) 287-2119 CONTACT: JON EASTHAM

NOTE: The underground utilities shown have been located from field survey information and existing drawings. The surveyor makes no guarantees that the underground utilities comprise all such utilities in the area, either in-service or abandoned. The surveyor further does not warrant that the underground utilities shown are in the exact location indicated although the surveyor does certify that they are located as accurately as possible from information available. The surveyor has not physically located the underground utilities.

CROSSROAD ENGINEERS, PC
115 N 17th AVENUE
BEECH GROVE, IN 46107
PHONE: (317) 780-1555
CONTACT: GREGORY J. ILKO
EMAIL: gilko@crossroadengineers.com

TITLE SHEET
CG HIGH SCHOOL BLACK BOX THEATER

BOOK 98, PAGE 451
PART OF THE WEST HALF OF THE NORTHWEST QUARTER OF SECTION FIFTEEN (15), TOWNSHIP THIRTEEN (13) NORTH, RANGE THREE (3) EAST OF THE SECOND PRINCIPAL MERIDIAN, DESCRIBED AS FOLLOWS:
BEGINNING AT THE NORTHWEST CORNER OF SAID HALF QUARTER SECTION; THENCE SOUTH ON THE WEST LINE THEREOF, TWENTY-FIVE (25) RODS; THENCE EAST AND PARALLEL WITH THE NORTH LINE OF SAID HALF QUARTER SECTION, TWENTY-SIX (26) RODS AND TWENTY-FOUR (24) LINKS; THENCE SOUTH AND PARALLEL TO THE WEST LINE OF SAID HALF QUARTER SECTION, THIRTY-SEVEN (37) RODS AND TWENTY (20) LINKS; THENCE EAST AND PARALLEL WITH THE NORTH LINE OF SAID HALF QUARTER SECTION, FIFTY-FIVE (55) RODS AND ONE (1) LINK, MORE OR LESS, TO THE EAST LINE OF SAID HALF QUARTER SECTION; THENCE NORTH, SIXTY-TWO (62) RODS AND TWENTY (20) LINKS TO THE NORTHEAST CORNER THEREOF; THENCE WEST, EIGHTY (80) RODS, MORE OR LESS, TO THE PLACE OF BEGINNING, CONTAINING TWENTY-FIVE (25) ACRES, MORE OR LESS.

REGISTERED PROFESSIONAL ENGINEER
GREGORY J. ILKO
STATE OF INDIANA
103005
CONSULTATION
APPROVED
DATE: FEBRUARY 07, 2023
BY: [Signature]

REVISIONS

NO.	DATE	BY	APPR.
1			
2			
3			
4			
5			
6			
7			
8			
9			




SHEET

100

100

DIRECTORY PATH : R:\Active\Center Grove Community School Corporation\Black Box\Design\CAD\Plans
DATE USER : 2/2/2023 9:00 AM / Dpesso

EXISTING UTILITY SIZE AND MATERIAL INFORMATION SHOWN ON THESE PLANS ARE PER THE BEST GRAPHICAL AND VISIBLE INFORMATION AVAILABLE. CONFLICTS MAY EXIST AND IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO FIELD VERIFY ALL SIZING AND MATERIAL INFORMATION PROVIDED. IF ACTUAL CONDITIONS DIFFER FROM THAT INFORMATION SHOWN ON THE PLANS, THE CONTRACTOR SHALL, PRIOR TO THE INSTALLATION OF ANY PROPOSED INFRASTRUCTURE, NOTIFY THE DESIGN ENGINEER IMMEDIATELY.



FLOODPLAIN INFORMATION

BY GRAPHIC PLOTTING ONLY, THIS TRACT OF LAND DESCRIBED HEREON LIES WITHIN ZONE "X" (AREAS OUTSIDE THE 500-YEAR FLOODPLAIN) AND IS NOT IN A SPECIAL HAZARD AREA AS PLOTTED ON THE FEDERAL EMERGENCY MANAGEMENT AGENCY FLOOD INSURANCE RATE MAP FOR JOHNSON COUNTY, INDIANA, COMMUNITY PANEL NO. 18081C01050, WHICH BEARS AN EFFECTIVE DATE OF 08/02/2007.

BENCHMARK INFORMATION

BM #1
ORIGINATING BENCHMARK
DESIGNATION - X 13
PID - KA0010
STATE/COUNTY - IN/MORGAN
USGS QUAD - MOORESVILLE EAST (1980)
VERT ORDER - FIRST CLASS II
DESCRIBED BY COAST AND GEODETIC SURVEY 1946
1.2 MI N FROM WAVERLY
IN JOHNSON COUNTY, 1.2 MILES NORTH ALONG STATE HIGHWAY 37 FROM THE INTERSECTION OF STATE HIGHWAY 144 AT WAVERLY, MORGAN COUNTY, 125 YARDS NORTH OF THE MORGAN-JOHNSON COUNTY LINE, 26 FEET WEST OF THE CENTERLINE OF THE HIGHWAY, IN LINE WITH THE WEST RIGHT-OF-WAY FENCE, 1.5 FEET SOUTH OF A WHITE WOODEN WITNESS POST, AND ABOUT 2 FEET HIGHER THAN THE HIGHWAY. A STANDARD DISK, STAMPED 686.370 X 13 1930 AND SET IN THE TOP OF A CONCRETE POST PROJECTING 7 INCHES ABOVE GROUND.
RECOVERY NOTE BY IN DEPT OF NAT RES 1985
NEW DESC- AT THE INTERSECTION OF NEW STATE ROAD 144 AND OLD STATE ROAD 37, IN THE SOUTHWEST QUARTER OF THE INTERSECTION, WITNESS POST IS GONE RIGHT-OF-WAY FENCE IS GONE, ALL OTHER INFORMATION APPEARS TO BE CORRECT.
ELEV. = 685.94 (NAVD 88)
TBM #423
"OUT BOX" ON NORTH SIDE OF FARTHEST WEST LIGHT POLE BASE ON SOUTH SIDE OF ROAD EAST OF SITE.
ELEV. = 749.32

LEGAL DESCRIPTION

BOOK 98, PAGE 451
PART OF THE WEST HALF OF THE NORTHWEST QUARTER OF SECTION FIFTEEN (15), TOWNSHIP THIRTEEN (13) NORTH, RANGE THREE (3) EAST OF THE SECOND PRINCIPAL MERIDIAN, DESCRIBED AS FOLLOWS:
BEGINNING AT THE NORTHWEST CORNER OF SAID HALF QUARTER SECTION; THENCE SOUTH ON THE WEST LINE THEREOF, TWENTY-FIVE (25) RODS; THENCE EAST AND PARALLEL WITH THE NORTH LINE OF SAID HALF QUARTER SECTION, TWENTY-SIX (26) RODS AND TWENTY-FOUR (24) LINKS; THENCE SOUTH AND PARALLEL TO THE WEST LINE OF SAID HALF QUARTER SECTION, THIRTY-SEVEN (37) RODS AND TWENTY (20) LINKS; THENCE EAST AND PARALLEL WITH THE NORTH LINE OF SAID HALF QUARTER SECTION, FIFTY-FIVE (55) RODS AND ONE (1) LINK, MORE OR LESS, TO THE EAST LINE OF SAID HALF QUARTER SECTION; THENCE NORTH, SIXTY-TWO (62) RODS AND TWENTY (20) LINKS TO THE NORTHEAST CORNER THEREOF; THENCE WEST, EIGHTY (80) RODS, MORE OR LESS, TO THE PLACE OF BEGINNING, CONTAINING TWENTY-FIVE (25) ACRES, MORE OR LESS.


UTILITIES

NOTE: Listed below are the Indiana Underground Plant Protection Services Contacts; Others not listed may exist.

SEWER GREENWOOD SANITATION 367 S. WASHINGTON ST. GREENWOOD, IN 46143 PHONE: (317) 888-1254 CONTACT: KEITH MEIER FIBER ZAYO 9209 CASTLE GATE DRIVE INDIANAPOLIS, IN 46236 PHONE: (765) 341-1199 CONTACT: WAYLON HIGGINS METRONET 3701 COMMUNICATIONS WAY EVANSVILLE, IN 47715 PHONE: (812) 213-1050 CONTACT: LORI KEMPER	WATER BARGERSVILLE WATER 24 N. MAIN STREET BARGERSVILLE, IN 46106 PHONE: (317) 422-3170 CONTACT: KEVIN KILLINGER TELEPHONE AT&T 240 N. MERIDIAN STREET INDIANAPOLIS, IN 46104 PHONE: (317) 265-3050 CONTACT: MATT SPINDLER FIRE DEPARTMENT BARGERSVILLE FIRE DEPARTMENT 3991 N. ST. RD. 135 BARGERSVILLE, IN 46106 PHONE: (317) 422-5187 CONTACT: KEVIN KILLINGER	CABLE COMCAST 1600 W. VERNAL PIKE BLOOMINGTON, IN 47404 PHONE: (812) 360-3090 CONTACT: STEVE McARTOR ELECTRIC JOHNSON COUNTY REMC 750 INTERNATIONAL DRIVE FRANKLIN, IN 46151 PHONE: (317) 738-7622 CONTACT: DOUG STAHL GAS CENTERPOINT ENERGY 1800 W. 26th STREET MUNCIE, IN 47302 PHONE: (765) 287-2119 CONTACT: JON EASTHAM
--	---	---

NOTE: The underground utilities shown have been located from field survey information and existing drawings. The surveyor makes no guarantees that the underground utilities comprise all such utilities in the area, either in-service or abandoned. The surveyor further does not warrant that the underground utilities shown are in the exact location indicated although the surveyor does certify that they are located as accurately as possible from information available. The surveyor has not physically located the underground utilities.

EXISTING LEGEND



CROSSROAD ENGINEERS, PC
TRANSPORTATION & DEVELOPMENT CONSULTANTS
115 S. 17th AVE. SUITE 200
MORGANVILLE, IN 47136
PHONE: (317) 938-1000
FAX: (317) 938-1001
WWW.CROSSROADENGINEERS.COM

TOPOGRAPHIC SURVEY & DEMOLITION PLAN



CG HIGH SCHOOL BLACK BOX THEATER

JOB NO.	DRAWN	DEP	DESIGNED	APPR.	CJ	CJ
DATE	FEBRUARY 07, 2023					



NO.	1	2	3	4	5	6	7	8	9
DATE									

REVISIONS	BY	APPR.

SHEET 200




SCALE: 1" = 5'



CONCRETE TERRACE NOTES

1. LIGHTING SHALL CONFORM TO JOHNSON COUNTY STANDARDS. CONTRACTOR SHALL COORDINATE WITH OWNER AND/OR JOHNSON COUNTY FOR ALL REQUIRED DETAILS AND SPECIFICATIONS.
2. CONTRACTOR SHALL NOTIFY OWNER, IF PROOF ROLL OF SUBGRADE FALLS, TO DETERMINE IF LINE STABILIZATION OF SUBGRADE IS NEEDED.
3. SIGNAGE SHALL INCLUDE ALL NECESSARY HARDWARE AND FITTINGS, INCLUDING 10 FT. OF 1/4 GAUGE GALVANIZED SIGN POST.
4. REFER TO ARCHITECTURAL PLANS FOR ADDITIONAL SIGNAGE. VERIFY CONFLICTS WITH OWNER.
5. CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING WITH APPLICABLE UTILITY COMPANIES FOR ALL SERVICE DIS-CONNECTS.
6. CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING TRAFFIC AND PROVIDING ALL NECESSARY FLAGMEN, BARRELS, SIGNAGE, ETC. DURING CONSTRUCTION. ALL APPLICABLE M.U.T.C.D. STANDARDS SHALL GOVERN THIS WORK.
7. CONTRACTOR SHALL COORDINATE WITH APPLICABLE UTILITY COMPANIES AND BUILDING PLANS FOR WATER, ELECTRIC, ETC. TELEPHONE CONDUIT.
8. ALL FIELD TIES OBTAINED DURING CONSTRUCTION MUST BE REPAIRED/CONNECTED TO NEW DRAINAGE FACILITIES.
9. EXISTING UTILITY SIZE AND MATERIAL INFORMATION SHOWN ON THESE PLANS ARE PER THE BEST GRAPHICAL AND VISIBLE INFORMATION AVAILABLE. CONFLICTS MAY EXIST AND IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO FIELD VERIFY ALL EXISTING MATERIAL INFORMATION PROVIDED. SECTION LOCATIONS AND MATERIAL INFORMATION SHOWN ON THESE PLANS, THE CONTRACTOR SHALL PRIOR TO THE INSTALLATION OF ANY PROPOSED INFRASTRUCTURE, NOTIFY THE DESIGN ENGINEER IMMEDIATELY.
10. CONTRACTOR TO COORDINATE DOMESTIC WATER SERVICE AND METER SIZE WITH MAP PLANS PRIOR TO INSTALLATION.
11. CONTRACTOR TO CONFIRM SIZE OF ELECTRICAL CONDUIT WITH JOHNSON COUNTY REMC AND JOHNSON PLANS. CONDUIT SHALL BE INSTALLED BENEATH PAVEMENT WITH SWEEPS AND PULL STRING AS NECESSARY PER MEP PLANS REMC REQUIREMENTS.
12. CONTRACTOR SHALL COORDINATE WITH JOHNSON COUNTY REMC FOR ALL GRADING, SITE, AND DRAINAGE PLANS. CONTRACTOR SHALL COORDINATE WITH THE ARCHITECT TO DETERMINE PROPOSED FOUNDATION EXPOSURE, HOWEVER, IN NO INSTANCE SHALL DRAINAGE TOWARDS THE BUILDING FOUNDATION BE ALLOWED.
13. CONTRACTOR PROPOSED ELECTRICAL SERVICE MAY BE REQUIRED BY STATE, COUNTY, OR LOCAL OFFICIALS.
14. CONTRACTOR TO COORDINATE WITH JOHNSON COUNTY REMC FOR NECESSARY ELECTRIC SERVICE REQUIREMENTS AND SPECIFICATIONS, AND BUILDING PLANS FOR ALL UTILITY SERVICE POINT LOCATIONS. CONTRACTOR SHALL ALSO COORDINATE WITH JOHNSON COUNTY REMC FOR ALL UTILITY SERVICE POINT LOCATIONS.
15. CONTRACTOR TO COORDINATE WITH BARGERSVILLE WATER FOR FIRE SERVICE AND METER VAULT INSTALLATION AND SPECIFICATIONS.
16. WATER SERVICE INSTALLATION SHALL BE IN ACCORDANCE WITH BARGERSVILLE WATER STANDARDS AND SPECIFICATIONS. CONTRACTOR SHALL COORDINATE WITH BARGERSVILLE WATER FOR PERMITTING, CONNECTION AND TESTING PROCEDURES AND REQUIREMENTS.
17. CONTRACTOR SHALL MAINTAIN A MINIMUM 18" SEPARATION AT ALL PROPOSED WATER AND STORM SEWER/SANITARY SEWER CROSSINGS.
18. PRIVATE WATER MAINS AND FIRE HYDRANTS TO BE INSTALLED PER NFPA 24, PRIVATE FIRE SERVICE MAINS AND THEIR APPURTENANCES, AND BARGERSVILLE WATER SPECIFICATIONS.
19. CONTRACTOR TO COORDINATE WITH BARGERSVILLE WATER FOR NECESSARY PAVING FOR THE INSTALLATION OF UNDERGROUND CONDUIT FOR ELECTRICAL, TELEPHONE, AND FIBER SERVICES TO THE BUILDING.
20. FIRE SUPPRESSION LINE SIZING TO BE CONFIRMED WITH MEP FIRE SUPPRESSION DESIGNER.
21. ALL PRIVATE SANITARY SEWER SHALL BE 18" OR 24" PVC.
22. ALL PRIVATE LATERALS SHALL HAVE TRACER REB INSTALLED ON THE TOP OF PIPE FROM THE UPSTREAM CONNECTION TO THE DOWNSPRAIN TERMINATION POINT.
23. CONTRACTOR SHALL COORDINATE WITH BARGERSVILLE WATER FOR PROPOSED PRIVATE FIRE HYDRANTS AND FDC ARE RED IN COLOR. ADDITIONALLY, THE BONNET SHALL BE PAINTED IN ACCORDANCE WITH NFPA STANDARD 291, WITH COLOR CODING BASED ON RATED FLOW CAPACITY, BLUE=1500 GPM OR MORE, GREEN=1000-1499 GPM, ORANGE=500-999 GPM, RED=499 GPM OR LESS.
24. PRIOR TO CONSTRUCTION, CONTRACTOR SHALL OBTAIN A SUPPLEMENTAL DEMAND FOR THE PROPOSED PRIVATE FIRE MAIN WILL PROVIDE ENOUGH WATER TO MEET THE CALCULATED SPRINKLER SYSTEM DEMAND FOR THE PROPOSED STRUCTURE.
25. PRIVATE FIRE MAINS MUST BE VISUALLY INSPECTED AND APPROVED BY BARGERSVILLE FIRE. PRIOR TO BACKFILL.
26. PRIOR TO CONSTRUCTION, CONTRACTOR SHALL OBTAIN A SUPPLEMENTAL DEMAND FOR THE PROPOSED PRIVATE FIRE MAIN AND THE NFPA RECORD OF COMPLETION MUST BE RECEIVED BEFORE A CERTIFICATE OF OCCUPANCY WILL BE ISSUED.

EXISTING LEGEND




ADDITIONAL EROSION CONTROL
MEASURES MAY BE REQUIRED BY
STATE, CITY OR COUNTY OFFICIALS

NOTE:
NO EARTHWORK DISTURBING ACTIVITY
MAY COMMENCE UNTIL A STORM WATER
MANAGEMENT PERMIT IS OBTAINED.

SITE DIMENSION LEGEND

- (A) MULCH SEEDING/LANDSCAPE AREAS
- (B) STRUCTURE FOUNDATION – PER BUILDING PLANS
- (C) 4" CONCRETE SIDEWALK (SEE DETAIL– SHEET 700)
- (J) SAWCUT
- (K) PAVEMENT REPAIR
- 1.5" HMA SURFACE 9.5mm, ON
VARIABLE DEPTH HMA BASE 25mm, ON
12" FLOWABLE MORTAR (SEE DETAIL– SHEET 700)
- (S) STAIRCASE (SEE DETAIL – SHEET ###)
- P.W. — P.W. — P.W. — PROPOSED WATER LINE
— P.W. — P.W. — P.W. — PROPOSED SANITARY LATERAL
DITCH LINE
STORM SEWER W/ MANHOLE & END SECTION
STORM INLETS
CLEANOUT
WATER BENDS
WATER VALVE
WATER LINE PLUG
WATER TEE




CONCRETE TERRACE DETAILS

CG HIGH SCHOOL BLACK BOX THEATER





JOB No.		DRAWN	DEP	CHECKED	GJJ
DATE	FEBRUARY 07, 2023	DESIGNED	DJM	APPR.	GJJ
					Transportation & Development Consultants 115 N. 7TH AVE., 8ED-506, N. 44TH (D7) 786-5800
					SHEET 301



SHEET		301		REVISIONS		BY	APPR.
NO.	DATE						
9							
8							
7							
6							
5							
4							
3							
2							
1							

[illegible]

DIRECTORY PATH : R:\Active\Center Grove Community School Corporation\Black Box\Design\CAO\Plans
DATE/USER : 2/2/2023 8:29 AM / J. Dipetta



PROPOSED LEGEND	
	SANITARY SEWER LATERAL WITH CLEANOUT
	STORM SEWER W/MANHOLE & END SECTION
	WATER LINE
	STORM INLET
	WATER TEE
	45° BEND
	22.5° BEND
	11.25° BEND

NOTE:
NO EARTHWORK DISTURBING ACTIVITY
MAY COMMENCE UNTIL A STORM WATER
MANAGEMENT PERMIT IS OBTAINED.



CROSSROAD
ENGINEERS, PC

TRANSPORTATION
Development Consultants
115 E. 17th Street, Suite 401
Indianapolis, IN 46204-4001

STORM PLAN & PROFILE

CG HIGH SCHOOL BLACK BOX THEATER

JOB No.

DATE

FEBRUARY 07, 2023

DESIGNED

DJM

CHECKED

CJJ

APPR.


CJJ

SHEET

401

NO.	DATE	REVISIONS	BY	APPR.
9				
8				
7				
6				
5				
4				
3				
2				
1				


DIRECTORY PATH : R:\Active\Center Grove Community School Corporation\Black Box\Design\CAD\Plans
DATE/USER : 1/11/2023 9:34 AM / Dpexoso



GRADING LEGEND			
X	860.00	TOP OF CURB	PROPOSED ELEVATIONS
X	859.50	EDGE OF PAVEMENT	
X	860.00	FINISH GRADE	EXISTING ELEVATIONS (TO BE FIELD VERIFIED)
X	860.00	*	
X	859.50	*	
X	860.00	*	PROPOSED FINISH FLOOR ELEVATION
	FFE = XXXXX		
---	800	EXISTING CONTOURS	PROPOSED CONTOURS
---	800	PROPOSED CONTOURS	

GRADING NOTES	
1. CONTRACTOR SHALL PROVIDE POSITIVE DRAINAGE AWAY FROM ALL BUILDINGS IN FINAL GRADING OF SITE. CONTRACTOR SHALL COORDINATE WITH THE ARCHITECT TO DETERMINE PROPER FOUNDATION EXPOSURE, HOWEVER, IN NO INSTANCE SHALL DRAINAGE TOWARDS THE BUILDING FOUNDATION BE ALLOWED.	

BENCHMARK INFORMATION	
BM #1 ORIGINATING BENCHMARK	
DESIGNATION - X 13 PID - KA0010 STATE/COUNTY - IN/MORGAN USGS QUAD - MOORESVILLE EAST (1980)	
VERT ORDER - FIRST CLASS II	
DESCRIBED BY COAST AND GEODETIC SURVEY 1946 1.2 MI N FROM WAVERLY IN JOHNSON COUNTY, 1.2 MILES NORTH ALONG STATE HIGHWAY 37 FROM THE INTERSECTION OF STATE HIGHWAY 144 AT WAVERLY, MORGAN COUNTY, 125 YARDS NORTH OF THE MORGAN-JOHNSON COUNTY LINE, 26 FEET WEST OF THE CENTERLINE OF THE HIGHWAY, IN LINE WITH THE WEST RIGHT-OF-WAY FENCE, 1.5 FEET SOUTH OF A WHITE WOODEN WITNESS POST, AND ABOUT 2 FEET HIGHER THAN THE HIGHWAY. A STANDARD DSK, STAMPED 686.370 X 13 1930 AND SET IN THE TOP OF A CONCRETE POST PROJECTING 7 INCHES ABOVE GROUND.	
RECOVERY NOTE BY IN DEPT OF NAT RES 1985 NEW DESC- AT THE INTERSECTION OF NEW STATE ROAD 144 AND OLD STATE ROAD 37, IN THE SOUTHWEST QUARTER OF THE INTERSECTION, WITNESS POST IS GONE RIGHT-OF-WAY FENCE IS GONE, ALL OTHER INFORMATION APPEARS TO BE CORRECT.	
ELEV. = 685.94 (NAVD 88)	
TBM #423 "CUT BOX" ON NORTH SIDE OF FARTHEST WEST LIGHT POLE BASE ON SOUTH SIDE OF ROAD EAST OF SITE.	
ELEV. = 749.32	



RAMP & STAIRS GRADING DETAIL A
SCALE: 1"=5'



CROSSROAD ENGINEERS, PC
TRANSPORTATION & DEVELOPMENT CONSULTANTS
115 E. 17th AVE. SUITE 200
MORGANVILLE, IN 46150
TEL: 317.261.1111
WWW.CROSSROADENGINEERS.COM

GRADING PLAN

CG HIGH SCHOOL BLACK BOX THEATER

DATE: FEBRUARY 07, 2023

DESIGNED: DJM

DRAWN: GJJ

CHECKED: GJJ

APPROVED: GJJ

JOB NO.

DATE

DESIGNED

DRAWN




CHECKED

APPROVED


500

SHEET


REVISIONS		DATE	BY	APPR.
9				
8				
7				
6				
5				
4				
3				
2				
1				
N.O.				





THERE SHALL BE NO DIRT, DEBRIS, OR STORAGE OF MATERIALS IN THE PARKING LOT. THE STORM WATER CATCHES SHALL BE PHASE II COMPLIANT. THE STAGING AREA TO INCLUDE NO POSTING, PORT-O-LETS, TRASH CONTAINER, AND YIELDING TRUCKS. CONTRACTOR TO SELECT SUITABLE LOCATION FOR STAGING AREA. ALL PORT-O-LETS MUST BE ANCHORED DOWN TO PREVENT SPILLS. CONTRACTOR AND INDIVIDUALS MUST BE AVAILABLE TO THE AGENCY AND AFTER 8:00 AM FOR RAIN EVENT. A LOG OF THE INSPECTION REPORTS MUST BE KEPT AND MADE AVAILABLE TO THE CITY INSPECTOR UPON REQUEST. CONTRACTOR SHALL BE REQUIRED TO REPAIR ALL ASPHALT PAVEMENT THAT BECOMES DEGRADED DUE TO CONSTRUCTION. THE CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE ILLINOIS CONSTRUCTION MEASURES SHALL BE IN ACCORDANCE WITH THE CURRENT ILLINOIS STORM WATER QUALITY MANUAL - PLANNING AND SPECIFICATION GUIDE FOR EFFECTIVE EROSION CONTROL AND POST-CONSTRUCTION WATER QUALITY (THE IDEM MANUAL). EROSION AND EROSION CONTROL MEASURES SHALL BE APPROVED BY COUNTY OR LOCAL JURISDICTIONAL AGENCY PRIOR TO THE START OF CONSTRUCTION. ALL FENCE MATERIAL SHALL BE NW5F-6 NON-WOVEN FABRIC OR AN APPROVED ALTERNATE. CONTRACTOR/PERMIT HOLDER MUST SCHEDULE AN ON-SITE PRE-CONSTRUCTION MEETING WITH THE COUNTY AND CITY ENGINEERS PRIOR TO THE START OF CONSTRUCTION. PRIOR TO ANY DOWNGRADING ACTIVITIES, CONTRACTOR/PERMIT HOLDER MUST MEET WITH THE JOHNSON COUNTY SWA COMPLIANCE AND ENFORCEMENT INSPECTOR. IF AN EXPORT OF SOLIDS MATERIALS SHALL OCCUR, A MODIFICATION OF THE SWPPP IS REQUIRED. ALL SITES MUST PLACE A CONTRACTOR'S/PERMIT HOLDER'S DISPLAY BOARD WHERE THE CONSTRUCTION STORMWATER GENERAL PERMIT (CSGP) AND SWPPP PERMIT MUST BE DISPLAYED. IF PLACEMENT OF DISPLAY BOARD IS WAIVED FOR AN INDIVIDUAL EROSION CONTROL, NO AND SWPPP PERMITS MUST BE DISPLAYED ON THE STRUCTURE. ALL WINDOWS, DOORS, AND SIGNAGE MUST BE PROTECTED. THE STATE AND COUNTY OFFICIALS CAN BE REQUIRED ADDITIONAL EROSION CONTROL MEASURES IN THE FIELD AS SITE CONDITIONS WARRANT. THE STATE AND COUNTY OFFICIALS MAY ENTER THE CONSTRUCTION SITE FOR AN EXAMINATION OF THE CONSTRUCTION STORMWATER CONTROL MEASURE ARE BEING ADEQUATELY MAINTAINED AFTER RAINFALL EVENTS. CONCRETE, WASTE WATER SHALL BE DISCHARGED INTO AN APPROVED ON-SITE TREATMENT SYSTEM. SUCH WASTE WATER SHALL BE RETAINED ON-SITE UNTIL WASTE WATER IS SOLIDIFIED FOR 48 HOURS. POST-CONSTRUCTION PAVEMENT INLET PROTECTION SHALL BE INSTALLED PRIOR TO THE COMPLETION AND FINAL INSPECTION/APPROVAL OF ANY PROJECT. CONNECTING TO AN EXISTING STORM SEWER STRUCTURE, THE STRUCTURE MUST BE PROPERLY DRAINED. TOTAL DISTURBED ACREAGE FOR THIS PROJECT IS APPROXIMATELY 0.331 AC.












parking and material staging.



The logo for the White River Alliance features a stylized blue and green wave graphic above the text "WHITE RIVER ALLIANCE" in a bold, sans-serif font. The word "ALLIANCE" is in a larger font size than "WHITE RIVER".





CROSSROAD ENGINEERS, PC
TRANSPORTATION
Development Consultants
115 N. 7TH AVE. SUITE 400 • DALLAS, TX 75201-3808

MISCELLANEOUS DETAILS

CG HIGH SCHOOL BLACK BOX THEATER

JOB NO.	DRAWN	DEP	CHECKED	APPR.	DATE
			GJJ	GJJ	FEBRUARY 07, 2023

DESIGNED BY: *Gregory J. Ilkko*

DATE: FEBRUARY 07, 2023

BY: _____


REVISIONS

NO.	DATE	DESCRIPTION
1		
2		
3		
4		
5		
6		
7		
8		
9		

SHEET

700

SHEET



EARTHWORK

1. SCOPE OF WORK
- A. EXTENT: THE WORK REQUIRED UNDER THIS SECTION CONSISTS OF ALL EXCAVATING, FILLING, ROUGH GRADING AND RELATED ITEMS NECESSARY TO COMPLETE THE WORK INDICATED ON THE DRAWINGS AND DESCRIBED IN THE SPECIFICATIONS. THE CONTRACTOR SHALL NOTIFY IN WRITING THE OWNER AND THE ENGINEER OF ANY CHANGES, ERRORS OR OMISSIONS FOUND ON THE PLANS OR IN THE FIELD. BEFORE WORK IS STARTED OR RESUMED.
1. IN GENERAL, THE ITEMS OF WORK TO BE PERFORMED UNDER THIS SECTION SHALL INCLUDE CLEARING AND GRUBBING, REMOVAL OF TREES AND STUMPS, STRIPPING AND STORAGE OF TOPSOIL, FILL, COMPACTION AND ROUGH GRADING OF ENTIRE SITE. ALL TREES SHALL BE REMOVED UNLESS OTHERWISE NOTED IN PLANS OR DIRECTED BY OWNER.
2. EXCAVATED MATERIAL THAT IS SUITABLE MAY BE USED FOR FILLS. ALL UNSUITABLE MATERIAL AND ALL SURPLUS EXCAVATED MATERIAL NOT REQUIRED SHALL BE REMOVED FROM THE SITE. THE LOCATION OF DUMP AND LENGTH OF HAUL SHALL BE THE CONTRACTOR'S RESPONSIBILITY.
3. PROVIDE AND PLACE ANY ADDITIONAL FILL MATERIAL FROM OFF THE SITE AS MAY BE NECESSARY TO PRODUCE THE GRADES REQUIRED. FILL OBTAINED FROM OFF SITE SHALL BE OF KIND AND QUALITY AS SPECIFIED FOR FILLS HEREIN AND THE SOURCE APPROVED BY THE OWNER.
4. THE CONTRACTOR SHALL ACCEPT THE SITE AS HE FINDS IT AND SHALL REMOVE ALL TRASH, RUBBISH AND DEBRIS FROM THE SITE PRIOR TO STARTING EXCAVATION
2. BENCHMARK
- A. MAINTAIN CAREFULLY ALL BENCH MARKS, MONUMENTS AND OTHER REFERENCE POINTS; IF DISTURBED OR DESTROYED, CONTRACTOR SHALL CONTACT ENGINEER.
3. REMOVAL OF TREES
- A. THE INTEGRITY OF THE TOPOGRAPHIC FEATURES (INCLUDING TREES) SHALL BE PERSEVERED AS MUCH AS POSSIBLE. THE CONTRACTOR SHALL COORDINATE WITH OWNER AND/OR ENGINEER PRIOR TO CLEARING THE SITE FOR CONSTRUCTION.
- B. ALL BRUSH, STUMPS, WOOD AND OTHER REFUSE FROM THE TREES REMOVED SHALL BE HAULED TO DISPOSAL AREAS OFF OF THE SITE. DISPOSAL BY BURNING SHALL NOT BE PERMITTED UNLESS PROPER PERMITS ARE OBTAINED (WHERE APPLICABLE).
4. HANDLING OF TOPSOIL
- A. REMOVE ALL ORGANIC MATERIAL FROM THE AREAS TO BE OCCUPIED BY BUILDINGS, ROADS, WALKS AND PARKING AREAS. PILE AND STORE TOPSOIL AT A LOCATION WHERE IT WILL NOT INTERFERE WITH CONSTRUCTION OPERATIONS. TOPSOIL SHALL BE REASONABLE FREE FROM SUBSOIL, DEBRIS, WEEDS, GRASS, STONES, ETC.
- B. AFTER COMPLETION OF SITE GRADING AND SUBSURFACE UTILITY INSTALLATION, TOPSOIL SHALL BE REPLACED IN AREAS DESIGNATED ON THE EROSION CONTROL PLAN FOR SEEDING AND/OR SOODING. ANY REMAINING TOPSOIL SHALL BE USED FOR FINISHED GRADING AROUND STRUCTURES AND LANDSCAPING AREAS.
5. DISPOSITION OF UTILITIES
- A. RULES AND REGULATIONS GOVERNING THE RESPECTIVE UTILITIES SHALL BE OBSERVED IN EXECUTING ALL WORK UNDER THIS SECTION.
- B. IF ANY UTILITIES ARE ENCOUNTERED BUT NOT SHOWN ON THE DRAWINGS, THE ENGINEER SHALL BE ADVISED BEFORE WORK IS CONTINUED.
- C. INACTIVE AND ABANDONED UTILITIES ENCOUNTERED IN EXCAVATING AND GRADING OPERATIONS SHALL BE REPORTED TO THE ENGINEER. THEY SHALL BE REMOVED, PLUGGED OR CAPPED AS DIRECTED BY THE UTILITY COMPANY OR THE ENGINEER.
- D. IT SHALL BE THE RESPONSIBILITY OF EACH CONTRACTOR TO VERIFY ALL EXISTING UTILITIES AND CONDITIONS PERTAINING TO HIS PHASE OF THE WORK. IT SHALL ALSO BE THE CONTRACTOR'S RESPONSIBILITY TO CONTACT THE OWNERS OF THE VARIOUS UTILITIES BEFORE WORK IS STARTED.
6. SITE GRADING
- A. GRADES: CONTRACTOR SHALL PERFORM ALL CUTTING, FILLING, COMPACTING OF FILLS AND ROUGH GRADING REQUIRED TO BRING ENTIRE PROJECT AREA TO GRADE AS SHOWN ON THE DRAWINGS.
- B. ROUGH GRADING: THE TOLERANCE FOR PAVED AREAS SHALL NOT EXCEED 0.10 FEET PLUS OR MINUS ABOVE THE ESTABLISHED SUBGRADE. ALL OTHER AREAS SHALL NOT EXCEED 0.10 FEET PLUS OR MINUS THE ESTABLISHED GRADE. ALL BANKS AND OTHER BREAKS IN GRADE SHALL BE ROUNDED AT THE TOP AND BOTTOM.
- C. COMPACTION REQUIREMENTS:
1. ALL BUILDING PAD AREAS SHALL BE COMPACTED TO STANDARDS SPECIFIED BY LOCAL AND/OR STATE BUILDING CODES.
2. COMPACTION REQUIREMENTS OF PAVED AREAS SHALL BE 95% OF MAXIMUM DRY DENSITY.
7. EARTH WORK BALANCE
- A. THE CONTRACTOR SHALL CONFIRM ALL EARTHWORK QUANTITIES PRIOR TO START OF CONSTRUCTION. IF AN EXCESS OR SHORTAGE OF EARTH IS ENCOUNTERED, THE CONTRACTOR SHALL CONFIRM WITH THE OWNER AND ENGINEER THE REQUIREMENTS FOR STOCKPILING, REMOVAL OR IMPORTING OF EARTH.
- MINOR ADJUSTMENTS TO THE GRADES MAY BE REQUIRED TO EARTHWORK BALANCES WHEN MINOR EXCESS MATERIAL OR SHORTAGES ARE ENCOUNTERED. IT IS RECOGNIZED BY THE PARTIES HERETO THAT THE CALCULATIONS OF THE ENGINEER IN ACCORDANCE WITH THE AMERICAN SOCIETY OF CIVIL ENGINEERS STANDARDS FOR SUCH CALCULATIONS. FURTHER, THAT THESE CALCULATIONS ARE SUBJECT TO THE INTERPRETATIONS OF SOIL BORINGS AS THE PHYSICAL LIMITS IN FINISH GRADE AND COMPACTION PERMITTED THE CONTRACTOR, AND THAT ALL OF THESE PARAMETERS MAY CAUSE EITHER AN EXCESS OR SHORTAGE OF ACTUAL EARTHWORK MATERIALS TO COMPLETE THE PROJECT. IF AN ACTUAL MINOR EXCESS OR SHORTAGE OF ACTUAL EARTHWORK MATERIALS OCCURS, THE CONTRACTOR SHALL CONTACT THE ENGINEER TO DETERMINE IF ADJUSTMENTS CAN BE MADE TO CORRECT THE IMBALANCE OF EARTH.

STREETSPARKING LOTS

1. SCOPE OF WORK
- A. THE WORK REQUIRED UNDER THIS SECTION INCLUDES ALL CONCRETE AND BITUMINOUS PAVING AND RELATED ITEMS NECESSARY TO COMPLETE THE WORK INDICATED ON THE DRAWINGS AND DESCRIBED IN THE SPECIFICATIONS, INCLUDING BUT NOT LIMITED TO:
1. ALL STREETS, PARKING AREAS WITHIN THE CONTRACT LIMITS.
2. CURBS AND CONCRETE RAMPS.
3. SIDEWALKS AND CONCRETE SLABS.
4. IN THE CASE OF ANY CONFLICTS WITH THESE SPECIFICATIONS AND LOCAL, STATE, FEDERAL SPECIFICATIONS THE MORE STRINGENT SHALL APPLY.
5. IN THE CASE OF ANY CONFLICTS WITH THESE SPECIFICATIONS AND LOCAL, STATE, FEDERAL SPECIFICATIONS THE MORE STRINGENT SHALL APPLY.
2. PAVEMENT CONSTRUCTION
- A. ALL STREET CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE PLANS AND SPECIFICATIONS AND CONFORM TO THE MINIMUM STANDARDS OF THE JOHNSON COUNTY PLANNING AND HIGHWAY DEPARTMENTS, AND IF THERE ARE AREAS UNDEFINED USE THE MOST CURRENT I.N.D.O.T. STANDARD SPECIFICATION.
- B. FLEXIBLE PAVEMENT
1. MATERIALS
- A. GENERAL: USE LOCALLY AVAILABLE MATERIALS AND GRADATIONS WHICH EXHIBIT A SATISFACTORY RECORD OF PREVIOUS INSTALLATIONS.
- B. COMPACTED AGGREGATE BASE: SOUND, ANGULAR CRUSHED LESTONE, CRUSHED OR UNCRUSHED GRAVEL, OR CRUSHED OR PROCESSED AIR-COOLED BLAST FURNACE SLAG. COURSE AGGREGATE SHALL BE CLASS A, TYPE "0" AND CONFORM TO THE MOST CURRENT I.N.D.O.T. STANDARD SPECIFICATION.
- C. BASE COURSE, AGGREGATE: SOUND, ANGULAR CRUSHED STONE, CRUSHED OR UNCRUSHED GRAVEL, OR CRUSHED SLAG, SAND, STONE, OR SLAG SCREENINGS. COARSE AGGREGATES SHALL BE CLASS A OR B AND CONFORM TO I.N.D.O.T. STANDARDS SPECIFICATIONS SECTION 903.
- D. COARSE AGGREGATE FOR SURFACE AND BINDER MIXTURES: CRUSHED STONE, CRUSHED GRAVEL, CRUSHED SLAB, AND SHARP EDGED NATURAL SAND. SURFACE COURSE AGGREGATES SHALL BE CLASS A AND CONFORM TO I.N.D.O.T. STANDARD SPECIFICATIONS SECTION 903.
- E. ASPHALT CEMENT: PETROLEUM ASPHALT CEMENT, AP 5 WITH PENETRATION OF 60-70 OR VISSCOSITY GRADED ASPHALT CEMENT AC-20 CONFORMING TO THE MOST CURRENT I.N.D.O.T. STANDARD SPECIFICATION.
- F. PRIME COAT: MEDIUM-CURE LIQUID ASPHALT OR ASPHALT EMULSION CONFORMING TO THE MOST CURRENT I.N.D.O.T. STANDARD SPECIFICATION.
- G. TACK COAT: RAPID-CURE LIQUID ASPHALT OR ASPHALT EMULSION CONFORMING TO THE MOST CURRENT I.N.D.O.T. STANDARD SPECIFICATION.
- H. LANE MARKING PAINT: CHLORINATED RUBBER-ALKYD TYPE, AASHTO M248 (FS TT-P-115), TYPE III.
3. ASPHALT-AGGREGATE MIXTURE
- A. ALL BITUMINOUS MIXTURES ARE TO CONFORM TO CURRENT I.N.D.O.T. SPECIFICATIONS
1. SURFACE COURSE: HMA SURFACE 9.5mm
2. BINDER COURSE: HMA INTERMEDIATE 19.0mm
3. BASE COURSE: TYPE HMA BASE 25.0mm
- **PROVIDED A JOB MIX FORMULA FOR EACH TYPE OF ASPHALT PRIOR TO THE BEGINNING OF THE CONSTRUCTION PROJECT.
4. SURFACE PREPARATION
- A. REMOVE LOOSE MATERIAL FROM COMPACTED SUBGRADE SURFACE IMMEDIATELY BEFORE APPLYING PRIME COAT.
- I) PROOF ROLL SUBGRADE SURFACE WITH LOADED TIR-AXLE TRUCK (48 HOUR NOTICE IS REQUIRED TO BE GIVEN TO THE JOHNSON COUNTY HIGHWAY DEPT.) TO CHECK FOR UNSTABLE AREAS AND AREAS REQUIRING ADDITIONAL COMPACTION.
- II) NOTIFY CONTRACTOR OF UNSATISFACTORY CONDITIONS. DO NOT BEGIN PAVING WORK UNTIL DEFICIENT SUBGRADE AREAS HAVE BEEN CORRECTED AND ARE READY TO RECEIVE PAVING.
- B. AGGREGATE BASE: AFTER PLACEMENT, PROOF ROLL COMPACTED AGGREGATE BASE SURFACE TO CHECK FOR UNSTABLE AREAS AND AREAS REQUIRING ADDITIONAL COMPACTION.
- I) NOTIFY CONTRACTOR OF UNSATISFACTORY CONDITIONS. DO NOT BEGIN PAVING WORK UNTIL DEFICIENT AGGREGATE BASE AREAS HAVE BEEN CORRECTED AND ARE READY TO RECEIVE PAVING.
- II) REMOVE LOOSE MATERIAL FROM COMPACTED AGGREGATE BASE SURFACE IMMEDIATELY BEFORE APPLYING PRIME COAT.
5. PLACING THE MIX
- A. GENERAL: PLACE BITUMINOUS AGGREGATE MIXTURE ON PREPARED SURFACE. SPREAD AND STRIKE-OFF. SPREAD MIXTURE AT MINIMUM TEMPERATURE OF 225 DEGREES F.(107 DEGREES C). PLACE INACCESSIBLE AND SMALL AREAS BY HAND. PLACE EACH COURSE TO REQUIRED GRADE, CROSS-SECTION, AND COMPACTED THICKNESS.
- B. BASE COURSE, COMPACTED AGGREGATE: SPREAD AND COMPACT IN TWO LIFTS AS FOLLOWS:
- I) FIRST LIFT: NO. 5'S SHALL BE A MINIMUM OF 4" OR ½ THE TOTAL DEPTH OF AGGREGATE. EXTEND THE FIRST LIFT 4" OR A DISTANCE EQUAL TO THE DEPTH OF THE LIFT BEYOND THE SECOND LIFT.
- II) SECOND LIFT: SIZE NO. 53
- C. PRIME COAT: SUBBASE SURFACE SHALL BE PRIMED IN ACCORDANCE WITH THE APPLICABLE REQUIREMENTS OF THE MOST CURRENT I.N.D.O.T. STANDARD SPECIFICATION.
- D. HOT ASPHALT CONCRETE BINDER COURSE: SPREAD AND ROLL TO MINIMUM FINISH DEPTHS INDICATED ON DETAILS.
- E. TACK COAT: BINDER COURSE SHALL BE TACKED PRIOR TO THE INSTALLATION OF THE SURFACE COURSE IN ACCORDANCE WITH THE APPLICABLE REQUIREMENTS OF THE MOST CURRENT I.N.D.O.T. STANDARD SPECIFICATION.

- F. SURFACE COURSE: SPREAD AND ROLL TO MINIMUM FINISH DEPTH INDICATED ON DETAILS. FINISH ELEVATION SHALL BE TRUE TO LINE AND GRADE WITHIN ¼" OF TRUE ELEVATIONS.
- G. PAVEMENT PLACING: PLACE IN STRIPS NOT LESS THAN 10' WIDE, UNLESS OTHERWISE ACCEPTABLE TO ARCHITECT/ENGINEER. AFTER FIRST STRIP HAS BEEN PLACED AND ROLLED, PLACE SUCCEEDING STRIPS AND EXTEND ROLLING TO OVERLAP PREVIOUS STRIPS. COMPLETE BINDER COURSE FOR A SECTION BEFORE PLACING SURFACE COURSE.
- H. JOINTS: MAKE JOINTS BETWEEN OLD AND NEW PAVEMENTS, OR BETWEEN PAVEN PASSSES, OR BETWEEN SUCCESSION DAYS WORK, TO ENSURE CONTINUOUS BOND BETWEEN ADJOINING WORK. CONSTRUCT JOINTS TO HAVE SAME TEXTURE, DENSITY AND SMOOTHNESS AS OTHER SECTIONS. CLEAN CONTACT SURFACES AND APPLY TACK COAT.
6. ROLLING
- A. GENERAL: BEGIN ROLLING WHEN MIXTURE WILL BEAR ROLLER WEIGHT WITHOUT EXCESSIVE DISPLACEMENT.
- I) COMPACT MIXTURE WITH HOT HAND TAMPERS OR VIBRATING PLATE COMPACTORS IN AREAS INACCESSIBLE TO ROLLERS.
- B. BREAKDOWN ROLLING: ACCOMPLISH BREAKDOWN OR INITIAL ROLLING IMMEDIATELY FOLLOWING ROLLING OF JOINTS AND OUTSIDE EDGE. CHECK SURFACE AFTER BREAKDOWN ROLLING, AND REPAIR DISPLACED AREAS BY LOOSENING AND FILLING, IF REQUIRED, WITH HOT MATERIAL.
- C. SECOND ROLLING: FOLLOW BREAKDOWN ROLLING AS SOON AS POSSIBLE, WHICH MIXTURE IS HOT. CONTINUE SECOND ROLLING UNTIL MIXTURE HAS BEEN THOROUGHLY COMPACTED.
- D. FINISH ROLLING: PERFORM FINISH ROLLING WHILE MIXTURE IS STILL WARM ENOUGH FOR REMOVAL OF ROLLER MARKS. CONTINUE ROLLING UNTIL ROLLER MARKS ARE ELIMINATED AND COURSE HAS ATTAINED MAXIMUM DENSITY.
- E. PATCHING: REMOVE AND REPLACE PAVING AREAS MIXED WITH FOREIGN MATERIALS AND DEFECTIVE AREAS. CUT OUT SUCH AREAS AND FILL WITH ROLLER BITUMINOUS AGGREGATE MIX. COMPACT BY ROLLING TO MAXIMUM SURFACE DENSITY AND SMOOTHNESS.
- F. PROTECTION: AFTER FINAL ROLLING, DO NOT PERMIT VEHICULAR TRAFFIC ON PAVEMENT UNTIL IT HAS COOLED AND HARDENED.
- G. ERECT BARRICADES TO PROTECT PAVING FROM TRAFFIC UNTIL MIXTURE HAS COOLED ENOUGH NOT TO BECOME MARKED.
7. TRAFFIC AND LANE MARKINGS
- A. CLEANING: SWEEP AND CLEAN SURFACE TO ELIMINATE LOOSE MATERIAL AND DUST.
- B. STRIPING: USE CHLORINATED RUBBER BASE TRAFFIC LAKE-MARKING PAINT, FACTORY MIXED, QUICK-DRYING, AND NON-BLEEDING. COLOR: YELLOW/WHITE/BLUE
- I) DO NOT APPLY TRAFFIC AND LANE MARKING PAINT UNTIL LAYOUT AND PLACEMENT HAS BEEN VERIFIED WITH ARCHITECT/ENGINEER.
- II) APPLY PAINT WITH MECHANICAL EQUIPMENT TO PRODUCE UNIFORM STRAIGHT EDGES. APPLY IN TWO COATS AT MANUFACTURER'S RECOMMENDED RATES.
8. FIELD QUALITY CONTROL
- A. TESTING AND INSPECTION SERVICE:
- I) OWNER SHALL EMPLOY A TESTING LABORATORY TO PERFORM PAVEMENT TESTING AND INSPECTION SERVICE FOR QUALITY CONTROL DURING PAVING OPERATIONS.
- II) TESTING SERVICE SHALL HAVE REPRESENTATIVE PRESENT TO OBSERVE AND PERFORM TESTS AT ALL TIMES PAVING WORK IS IN PROGRESS.
- B. GENERAL: TESTING SERVICE REPRESENTATIVE SHALL TAKE A MINIMUM OF TWO SAMPLES PER LIFT OF BITUMINOUS AGGREGATE MIX EACH DAY BEFORE PAVING OPERATION. LABORATORY TEST SHALL BE PERFORMED ON THESE SAMPLES TO DETERMINE AGGREGATE GRADATION AND ASPHALT CONTENT
- I) TEST IN-PLACE COMPACTED BITUMINOUS AGGREGATE MIX COURSES FOR COMPLIANCE WITH REQUIREMENTS FOR THICKNESS, DENSITY AND AIR VOIDS AND SURFACE SMOOTHNESS. REPAIR OR REMOVE AND REPLACE UNACCEPTABLE PAVING AS DIRECTED BY ENGINEER.
- II) A TEST SECTION AT A MINIMUM SIZE OF 100'X12' SHALL BE PLACED AT A LOCATION AS DIRECTED BY THE COUNTY PRIOR TO FULL PRODUCTION FOR EACH TYPE OF MIX. THE TEST SECTION SHALL BE COMPACTED TO DETERMINE A TARGET DENSITY FOR THE REMAINDER OF THE PAVEMENT.
- C. THICKNESS: IN-PLACE COMPACTED THICKNESS WILL NOT BE ACCEPTABLE IF EXCEEDING FOLLOWING ALLOWABLE VARIATION FROM REQUIRED THICKNESS
- AGGREGATE BASE COURSE: ¾", PLUS OR MINUS
- BASE COURSE: ¾", PLUS OR MINUS
- BINDER COURSE: ¾", PLUS OR MINUS
- SURFACE COURSE: ¾", PLUS OR MINUS
- I) TESTING SERVICE SHALL SUBMIT CERTIFIED RESULTS TO THE OWNER AND ARCHITECT/ENGINEER WITHIN 72 HOURS AFTER TESTS ARE MADE, WITH THEIR COMMENTS AND RECOMMENDATIONS FOR ACTION.
- II) PAVEMENT WHICH FAILS TO COMPLY WITH APPROVED JOB MIX FORMULA SHALL BE REPLACED AS DIRECTED BY THE ARCHITECT/ENGINEER.
- E. SURFACE SMOOTHNESS: TEST FINISHED SURFACE FOR SMOOTHNESS, USING 10' STRAIGHTEDGE APPLIED PARALLEL WITH, AND AT RIGHT ANGLES TO CENTERLINE OF PAVED AREA. SURFACE WILL NOT BE ACCEPTABLE IF EXCEEDING THE FOLLOWING TOLERANCES FOR SMOOTHNESS.
- AGGREGATE BASE COURSE SURFACE:1/4"
- BASE COURSE SURFACE: 1/4"
- BINDER COURSE SURFACE: 1/8"
- WEARING COURSE SURFACE: 1/8"
- I) CHECK SURFACED AREAS AT INTERVALS AS DIRECTED BY TESTING SERVICE.
- F. DENSITY TESTS: DENSITY TESTS SHALL BE MADE AT EACH LIFT. TEST SHALL BE AS FOLLOWS:
- I) TESTS WILL BE REQUIRED AT VARIOUS TIMES AND LOCATIONS FOR SUBGRADE AND BASE COURSES FOR ASPHALT PAVING AREAS.
- G. TESTING SERVICE SHALL SUBMIT CERTIFIED RESULTS TO THE OWNER AND ENGINEER WITHIN 72 HOURS AFTER TESTS ARE MADE WITH THEIR COMMENTS AND RECOMMENDATIONS FOR ACTION.
- I) SUBGRADE SHALL BE PREPARED IN ACCORDANCE WITH THE MOST CURRENT I.N.D.O.T. STANDARD SPECIFICATION. NO TRAFFIC SHALL BE PERMITTED ON THE PREPARED SUBGRADE PRIOR TO PAVING.
- II) SEE SITE GRADING, UNDER THE 'EARTHWORK' SECTION FOR ADDITIONAL COMPACTION REQUIREMENTS.
9. APPLICATION
- A. GRADING: DO ANY NECESSARY GRADING IN ADDITION TO THAT PERFORMED IN ACCORDANCE WITH EARTHWORK SECTION TO BRING SUBGRADES, AFTER FINAL COMPACTION, TO THE REQUIRED GRADES AND SECTIONS FOR SITE IMPROVEMENTS.
- B. PREPARATION OF SUBGRADE: REMOVE SPONGY AND OTHERWISE UNSUITABLE MATERIAL AND REPLACE WITH STABLE MATERIAL. NO TRAFFIC WILL BE ALLOWED ON PREPARED SUBGRADE PRIOR TO PAVING.
- C. COMPACTION OF SUBGRADES: THE FIRST 6 INCHES BELOW THE SUBGRADE SHALL BE COMPACTED TO AT LEAST 100% OF THE MAXIMUM DRY DENSITY AS DETERMINED BY THE PROVISIONS OF AASHTO T-99. SURFACE SHALL BE PREVENTED FROM STANDING ON THE COMPACTED SUBGRADE.
- D. UTILITY STRUCTURES: CHECK FOR CORRECT ELEVATION OF ALL MANHOLE COVERS, VALVE BOXES AND SIMILAR STRUCTURES LOCATED WITHIN AREAS TO BE PAVED, AND MAKE, OR HAVE MADE, ANY NECESSARY ADJUSTMENTS IN SUCH STRUCTURES.
- E. PLACING CONCRETE
1. SUBGRADE: PLACE CONCRETE ONLY ON A MOIST, COMPACTED SUBGRADE OR BASE FREE FROM LOOSE MATERIAL. PLACE NO CONCRETE ON A MUDGY OR FROZEN SUBGRADE.
2. FORMS: ALL FORMS SHALL BE FREE FROM WARP, TIGHT ENOUGH TO PREVENT LEAKAGE AND SUBSTANTIAL ENOUGH TO MAINTAIN THEIR SHAPE AND POSITION WITHOUT SPRINGING OR SETTLING, WHEN CONCRETE IS PLACED. FORMS SHALL BE CLEAN AND SMOOTH IMMEDIATELY BEFORE CONCRETING.
3. PLACING CONCRETE: CONCRETE SHALL BE DEPOSITED SO AS TO REQUIRE AS LITTLE REHANDLING AS PRACTICABLE. WHEN CONCRETE IS TO BE PLACED AT AN ATMOSPHERIC TEMPERATURE OF 35 DEGREES F. OR LESS, THE MOST CURRENT I.N.D.O.T. STANDARD SPECIFICATIONS SHALL BE FOLLOWED.
- F. CONCRETE CURB
1. EXPANSION JOINTS: SHALL BE 1/2 INCH THICK PREMOULDED AT ENDS OF ALL RETURNS AND AT A MAXIMUM SPACING OF 100 FEET.
2. CONTRACTION JOINTS UNLESS OTHERWISE PROVIDED, CONTRACTION JOINTS SHALL BE SAWN JOINTS SPACED 10 FEET ON CENTER.
3. FINISH: TAMP AND SCREED CONCRETE AS SOON AS PLACED, AND FILL ANY HONEY COMBED PLACES. FINISH SQUARE CORNERSTONE 1/4 INCH RADIUS AND OTHER CORNERS TO RADI SHOWN.
- G. CONCRETE WALKS AND EXTERIOR STEPS
1. SLOPES: PROVIDE ¼ INCH PER FOOT CROSS SLOPE. MAKE ADJUSTMENTS ON SLOPES AT WALK INTERSECTIONS AS NECESSARY TO PROVIDE PROPER DRAINAGE.
2. DIMENSIONS: WALKS AND STEPS SHALL BE ONE COURSE CONSTRUCTION AND OF WIDTHS AND DETAILS SHOWN ON THE DRAWINGS.
3. FINISH: SCREED CONCRETE AND TROWEL WITH A STEEL TROWEL TO A HARD DENSE SURFACE AFTER SURFACE WATER HAS DISAPPEARED. APPLY MEDIUM BROOM FINISH AND SCRIBE TRANSVERSE JOINTS AT 6 FOOT SPACING. FLOWLINE, PROVIDE ½ INCH EXPANSION JOINTS WHERE SIDEWALKS INTERSECT, AND AT A MAXIMUM SPACING OF 48 FEET BETWEEN EXPANSION JOINTS.
- H. CURING CONCRETE FOR WALKS AND CURBS: EXCEPT AS OTHERWISE SPECIFIED, CURE ALL CONCRETE BY ONE OF THE METHODS DESCRIBED IN THE MOST CURRENT I.N.D.O.T. STANDARD SPECIFICATION.
- I. BITUMINOUS PAVEMENT: HOT MIX ASPHALT PAVEMENT SHALL BE AS SPECIFIED IN THE MOST CURRENT I.N.D.O.T. STANDARD SPECIFICATION. PAVING WILL NOT BE PERMITTED DURING UNFAVORABLE WEATHER OR THEN THE TEMPERATURE IS 40 DEGREES F. AND FALLING.
- J. COMPACTED AGGREGATE SUBBASE: THE THICKNESS SHOWN ON THE DRAWINGS IS THE MINIMUM THICKNESS OF THE FULL COMPACTED SUBBASE. COMPACTION SHALL BE ACCOMPLISHED BY ROLLING WITH A SMOOTH WHEELED ROLLER WEIGHING 8 TO 10 TONS, COMPACT TO 95% COMPACTION USING STANDARD TESTING PROCEDURES. ALONG CURBS, HEADERS AND WALLS AND AT ALL PLACES NOT ACCESSIBLE TO THE ROLLER, THE AGGREGATE MATERIAL SHALL BE TAMPED WITH MECHANICAL TAMPERS OR WITH APPROVED HAND TAMPERS.
- K. CONCRETE RAMPS
1. CONCRETE RAMPS FOR THE DISABLED SHALL BE REQUIRED AS SPECIFIED IN THE PLANS AND SHALL CONFORM WITH CURRENT SPECIFICATIONS ESTABLISHED BY THE AMERICAN DISABILITIES ACT (ADA), SECTION 4.7, "CURB RAMPS".
2. THE CONCRETE RAMP SHALL BE FLUSH AND FREE OF ABRUPT CHANGES WITH SIDEWALKS, OUTTERS OR STREETS, AND PROVIDE A MAXIMUM SLOPE OF 1:12.
3. THE MINIMUM WIDTH OF A CONCRETE RAMP SHALL BE (48) INCHES EXCLUSIVE OF FLARED SIDES.
4. SIDES OF CONCRETE RAMPS SHALL HAVE FLARED SIDES AS SHOWN IN THE PLANS.

STORM SEWER SYSTEMS


1. SCOPE OF WORK
- A. THE WORK UNDER THIS SECTION INCLUDES ALL STORM SEWERS, STORM WATER INLETS, AND RELATED ITEMS, INCLUDING EXCAVATING AND BACKFILLING NECESSARY TO COMPLETE THE WORK SHOWN ON THE DRAWINGS.
- B. IN THE CASE OF ANY CONFLICTS WITH THESE SPECIFICATIONS AND LOCAL, STATE, FEDERAL SPECIFICATIONS THE MORE STRINGENT SHALL APPLY.
2. STORM SEWER CONSTRUCTION
- A. STORM SEWERS
1. STORM SEWER STRUCTURES SHALL COMPLY WITH CURRENT SPECIFICATIONS OF THE JOHNSON COUNTY PLANNING AND ALL OTHER RESPONSIBLE AGENCIES IN RESPECT TO DESIGN AND QUALITY OF CONSTRUCTION.
2. ALL STORM SEWER CONSTRUCTION INSIDE PUBLIC RIGHT-OF-WAY, EITHER EXISTING OR TO BE DEDICATED, SHALL BE IN ACCORDANCE WITH THE MOST CURRENT I.N.D.O.T. STANDARD SPECIFICATION.
3. WHERE REINFORCED CONCRETE PIPE IS SHOWN ON THE CONSTRUCTION PLANS, IT SHALL BE IN ACCORDANCE WITH A.S.T.M. C-76 CLASS II WALL "C" UNLESS OTHERWISE SPECIFIED ON THE PLANS.
4. WHERE CORRUGATED METAL PIPE IS SHOWN ON THE CONSTRUCTION PLANS, IT SHALL BE 14 GAUGE ALUMINIZED UNLESS OTHERWISE SPECIFIED AND SHALL HAVE THE CONNECTING BANDS AND SEALS AS SPECIFIED BY THE MANUFACTURER. C.M.P. SHALL BE ALUMINIZED PIPE IN ACCORDANCE WITH A.S.T.M. A-444.
5. MANHOLES, CATCH BASINS AND INLETS SHALL BE PRECAST CONCRETE.
- A. IF THE CONTRACTOR ELEGTS TO USE ALTERNATE PRECAST STRUCTURES, HE SHALL SUBMIT SHOP DRAWINGS TO THE ENGINEER PRIOR TO ANY CONSTRUCTION.
6. PRECAST CONCRETE AND STEEL FOR MANHOLES AND INLETS SHALL BE IN ACCORDANCE WITH A.S.T.M. C-478.
7. CASTINGS SHALL BE AS SHOWN ON THE DETAIL SHEET(S) FOR MANUFACTURER, TYPE AND MODEL NUMBER.
8. GRANULAR BACKFILL SHALL BE REQUIRED UNDER ALL PAVEMENT AREAS AND TRENCHES WITHIN FIVE(5) FEET OF THE EDGE OF PAVEMENT.
9. ALL TRENCHES UNDER PAVEMENT SHALL BE COMPACTED TO 95 PERCENT MODIFIED PROCTOR.
- APPLICATION
- A. PERMITS AND CODES: THE INTENT OF THIS SECTION OF THE SPECIFICATIONS IS THAT THE CONTRACTOR'S BID ON THE WORK COVERED HEREIN SHALL BE BASED UPON THE DRAWINGS AND SPECIFICATIONS BUT THAT THE WORK SHALL COMPLY WITH ALL APPLICABLE CODES AND REGULATIONS AS AMENDED BY ANY WAIVERS. THE CONTRACTOR SHALL FURNISH ALL BONDS NECESSARY TO GET PERMITS FOR CUTS AND CONNECTIONS TO EXISTING SEWERS.
- B. LOCAL STANDARDS: THE TERM "LOCAL STANDARDS" AS USED HEREIN MEANS THE STANDARDS OF DESIGN AND CONSTRUCTION OF THE RESPECTIVE MUNICIPAL DEPARTMENT OR UTILITY COMPANY.
- C. EXISTING IMPROVEMENTS: THE CONTRACTOR SHALL MAINTAIN IN OPERATING CONDITION ALL ACTIVE UTILITIES, SEWERS AND OTHER DRAINS ENCOUNTERED IN THE SEWER INSTALLATION. THE CONTRACTOR SHALL REPAIR TO THE SATISFACTION OF THE OWNER ANY DAMAGE TO EXISTING ACTIVE IMPROVEMENTS.
- D. WORKMANSHIP: THIS WORK SHALL CONFORM TO ALL LOCAL, STATE AND NATIONAL CODES AND TO BE APPROVED BY ALL LOCAL AND STATE AGENCIES HAVING JURISDICTION.
- E. TRENCHING: LAY ALL PIPE IN OPEN TRENCHES, EXCEPT WHEN THE LOCAL AUTHORITY GIVES WRITTEN PERMISSION FOR TUNNELING. OPEN THE TRENCH SUFFICIENTLY AHEAD OF PIPE-LAYING TO REVEAL ANY OBSTRUCTIONS. THE MIN. WIDTH OF TRENCH SHALL BE 1.25 TIMES THE OUTSIDE DIA. OF PIPE. SHEET AND BRACE TRENCH AS NECESSARY TO PROTECT WORKMEN AND ADJACENT STRUCTURES. ALL TRENCHING TO COMPLY WITH OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION STANDARDS. KEEP TRENCHES FREE FROM WATER WHILE CONSTRUCTION IS IN PROGRESS. UNDER NO CIRCUMSTANCES SHALL PIPE OR APPURTENANCES BE LAID IN STANDING WATER. CONDUCT THE DISCHARGE FROM TRENCH DE-WATERING TO DRAINS OR NATURAL DRAINAGE CHANNELS.
- F. SPECIAL SUPPORTS: WHENEVER, IN THE OPINION OF THE ENGINEER, THE SOIL AT OR BELOW THE PIPE GRADE IS UNSUITABLE FOR SUPPORTING SEWERS AND APPURTENANCES SPECIFIED IN THIS SECTION, SUCH SPECIAL SUPPORT, IN ADDITION TO THOSE SHOWN OR SPECIFIED, SHALL BE PROVIDED AS THE ENGINEER MAY DIRECT, AND THE CONTRACT WILL BE ADJUSTED.
- G. BACKFILLING: BACKFILL SHALL BE PLACED AS SHOWN IN THE PLANS. NOTE THAT PVC & HDPE PIPE SHALL BE COVERED WITH 12" MINIMUM OF #8 STONE. COMPACT THIS BACKFILL THOROUGHLY, TAKING CARE NOT TO DISTURB THE PIPE. BACKFILL UNDER AND WITHIN 5 FEET OF WALKS, PARKING AREAS, DRIVEWAYS AND STREETS SHALL BE "B" BORROW OR EQUIVALENT GRANULAR MATERIAL ONLY AND THOROUGHLY COMPACTED BY APPROVED METHODS.
- H. MANHOLE INVERTS: CONSTRUCT MANHOLE FLOW CHANNELS OF CONCRETE SEWER PIPE OR BRICK, SMOOTHLY FINISHED, OF SEMICIRCULAR SECTION CONFORMING TO THE INSIDE DIAMETER OF THE CONNECTING SEWERS. MAKE CHANGES IN SIZE OR GRADE GRADUALLY AND CHANGES INDIRECTION BY TRUE CURVES. PROVIDE SUCH CHANNELS FOR ALL CONNECTING SEWERS AT EACH MANHOLE.
- I. SUBDRAINS: ALL SUBDRAINS SHALL BE OF THE SIZE SHOWN ON THE PLANS AND SHALL BE CONSTRUCTED TO THE GRADES SHOWN. ALL DRAINS CONSTRUCTED OFF-SITE AS PART OF THE OUTLET DRAIN WILL BE LOCATED AS SHOWN.
- J. UTILITIES: IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY ALL EXISTING UTILITIES AND CONDITIONS PERTAINING TO HIS WORK. IT SHALL ALSO BE THE CONTRACTOR'S RESPONSIBILITY TO CONTACT THE OWNERS OF THE VARIOUS UTILITIES BEFORE WORK IS STARTED. THE CONTRACTOR SHALL NOTIFY IN WRITING THE OWNER AND THE ENGINEER OF ANY CHANGES, ERRORS OR OMISSIONS FOUND ON THESE PLANS OR IN THE FIELD BEFORE WORK IS STARTED OR RESUMED.

WATER LINE SYSTEM

1. SCOPE OF WORK
- A. THE WORK UNDER THIS SECTION INCLUDES ALL WATER MAIN, FIRE HYDRANTS, SERVICES AND RELATED ITEMS, INCLUDING EXCAVATING AND BACKFILLING NECESSARY TO COMPLETE THE WORK SHOWN ON THE DRAWINGS.
2. MATERIALS
- A. ALL MATERIALS SHALL CONFORM TO ALL LOCAL, STATE, AND NATIONAL CODES AND SHALL BE APPROVED BY ALL LOCAL AND STATE AGENCIES HAVING JURISDICTION.
3. APPLICATION
- A. PERMITS AND CODES: THE INTENT OF THIS SECTION OF THE SPECIFICATIONS IS THAT THE CONTRACTOR'S BID ON THE WORK COVERED HEREIN SHALL BE BASED UPON THE DRAWINGS AND SPECIFICATIONS BUT THAT THE WORK SHALL COMPLY WITH ALL APPLICABLE CODES AND REGULATIONS AS AMENDED BY ANY WAIVERS. THE CONTRACTOR SHALL FURNISH ALL BONDS NECESSARY TO GET PERMITS FOR CUTS AND CONNECTIONS TO EXISTING WATER MAINS.
- B. LOCAL STANDARDS: THE TERM "LOCAL STANDARDS" AS USED HEREIN MEANS THE STANDARDS OF DESIGN AND CONSTRUCTION OF THE RESPECTIVE MUNICIPAL DEPARTMENT OR UTILITY COMPANY.
- C. EXISTING IMPROVEMENTS: THE CONTRACTOR SHALL MAINTAIN IN OPERATING CONDITION ALL ACTIVE UTILITIES, SEWERS AND OTHER DRAINS ENCOUNTERED IN THE WATER LINE INSTALLATION. THE CONTRACTOR SHALL REPAIR TO THE SATISFACTION OF THE OWNER ANY DAMAGE TO EXISTING ACTIVE IMPROVEMENTS.
- D. WORKMANSHIP: THIS WORK SHALL CONFORM TO ALL LOCAL, STATE AND NATIONAL CODES AND TO BE APPROVED BY ALL LOCAL AND STATE AGENCIES HAVING JURISDICTION. THIS INCLUDES ALL REQUIRED CLEANING AND TESTING PROCEDURES REQUIRED BY THE STATE AND LOCAL AGENCIES.
- E. TRENCHING: LAY ALL PIPE IN OPEN TRENCHES, EXCEPT WHEN THE LOCAL AUTHORITY GIVES WRITTEN PERMISSION FOR TUNNELING. OPEN THE TRENCH SUFFICIENTLY AHEAD OF PIPE-LAYING TO REVEAL ANY OBSTRUCTIONS. THE MIN. WIDTH OF TRENCH SHALL BE 1.25 TIMES THE OUTSIDE DIA. OF PIPE. SHEET AND BRACE TRENCH AS NECESSARY TO PROTECT WORKMEN AND ADJACENT STRUCTURES. ALL TRENCHING TO COMPLY WITH OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION STANDARDS. KEEP TRENCHES FREE FROM WATER WHILE CONSTRUCTION IS IN PROGRESS. UNDER NO CIRCUMSTANCES SHALL PIPE OR APPURTENANCES BE LAID IN STANDING WATER. CONDUCT THE DISCHARGE FROM TRENCH DE-WATERING TO DRAINS OR NATURAL DRAINAGE CHANNELS.
- F. SPECIAL SUPPORTS: WHENEVER, IN THE OPINION OF THE ENGINEER, THE SOIL AT OR BELOW THE PIPE GRADE IS UNSUITABLE FOR SUPPORTING PIPE AND APPURTENANCES SPECIFIED IN THIS SECTION, SUCH SPECIAL SUPPORT, IN ADDITION TO THOSE SHOWN OR SPECIFIED, SHALL BE PROVIDED AS THE ENGINEER MAY DIRECT, AND THE CONTRACT WILL BE ADJUSTED.
- G. BACKFILLING: BACKFILL SHALL BE PLACED AS SHOWN IN THE PLANS. NOTE THAT PVC & HDPE PIPE SHALL BE COVERED WITH 12" MINIMUM OF #8 STONE. COMPACT THIS BACKFILL THOROUGHLY, TAKING CARE NOT TO DISTURB THE PIPE. BACKFILL UNDER AND WITHIN 5 FEET OF WALKS, PARKING AREAS, DRIVEWAYS AND STREETS SHALL BE "B" BORROW OR EQUIVALENT GRANULAR MATERIAL ONLY AND THOROUGHLY COMPACTED BY APPROVED METHODS.
- H. UTILITIES: IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY ALL EXISTING UTILITIES AND CONDITIONS PERTAINING TO HIS WORK. IT SHALL ALSO BE THE CONTRACTOR'S RESPONSIBILITY TO CONTACT THE OWNERS OF THE VARIOUS UTILITIES BEFORE WORK IS STARTED. THE CONTRACTOR SHALL NOTIFY IN WRITING THE OWNER AND THE ENGINEER OF ANY CHANGES, ERRORS OR OMISSIONS FOUND ON THESE PLANS OR IN THE FIELD BEFORE WORK IS STARTED OR RESUMED.


SANITARY SEWER SYSTEMS

1. SCOPE OF WORK
- A. THE WORK UNDER THIS SECTION INCLUDES ALL SANITARY SEWERS, MANHOLES, CLEANOUTS AND RELATED ITEMS INCLUDING EXCAVATING AND BACKFILLING NECESSARY TO COMPLETE THE WORK SHOWN IN THE DRAWINGS, STARTING OUTSIDE THE BUILDING WALLS. THE END OF SEWERS SHALL BE TIGHTLY PLUGGED OR CAPPED AT THE TERMINAL POINTS, ADJACENT TO THE BUILDING DRAIN AS SPECIFIED IN THE PLUMBING INSTALLATIONS AND/OR ARCHITECTURAL DRAWINGS.
2. MATERIALS
- A. SANITARY SEWERS
1. ALL GRAVITY PLASTIC SEWER PIPE FITTINGS SHALL CONFORM TO ASTM D3034 WITH A CELL CLASSIFICATION OF 1454-B OR 12454-C. FLEXIBLE CASKTED COMPRESSION JOINTS SHALL BE USED FOR PVC & PVC TRUSS PIPE. NO SOLVENT CEMENT JOINTS SHALL BE ALLOWED.
2. ABS SEWER PIPE AND FITTINGS SHALL CONFORM TO ASTM D2680 LATEST REVISION.
3. TRACER WIRE SHALL BE INSTALLED WITH ALL NEW SANITARY PIPE.
- B. MANHOLES
1. PRECAST REINFORCED CONCRETE MANHOLE SECTIONS AND STEPS SHALL CONFORM TO ASTM C-478 LATEST REVISION. EXTERIOR OF THE MANHOLE SHALL BE WATERPROOFED WITH BISMATIC MATERIAL.
2. CASTING SHALL BE OF UNIFORM QUALITY, FREE FROM BLOW HOLES, POROSITY, HARD SPOTS, SHRINKAGE DISTORTION OR OTHER DEFECTS. THEY SHALL BE SMOOTH AND WELL-CLEANED BY SHOT-BLASTING OR BY SOME OTHER APPROVED METHOD. THEY SHALL BE COATED WITH ASPHALT PAINT WHICH SHALL RESULT IN A SMOOTH COATING, TOUGH AND TENACIOUS WHEN COLD, NOT TACKY OR BRITTLE. THEY SHALL BE GRAY IRON MEETING ASTM A-48 LATEST REVISION. MANHOLE COVERS FOR SANITARY SEWER SHALL BE NEEHAW TYPE R-1077-A W/R-7172-B-SP FRAME W/SELF-SEALING APPLICATION.
3. JOINTS: MANHOLE SECTIONS SHALL BE JOINED WITH A NOMINAL ½ INCH SIZE BUTYL RUBBER BASE CASKET MATERIAL, CONFORMING TO AASHTO M-198 AND FEDERAL SPECIFICATION SS-S-210A. JOINT CONFORMS TO ASTM C-443.
4. MANHOLES SHALL INCLUDE STEPS. SANITARY SEWER STANDARDS REVISIONS SHALL BE THAT STEPS ARE TO BE POLYPROPYLENE COATED STEEL REINFORCING OR AN APPROVED NON-CORROSIVE FIBERGLASS MATERIAL. THE LOCATION OF POLYPROPYLENE SHALL MEET THE REQUIREMENTS OF ASTM D2680. DEFORMED ¾ INCH DIAMETER OR LARGER REINFORCING STEEL CONFORMING TO ASTM A-615, GRADE 60, STEPS SHALL BE A MAXIMUM OF 24 INCHES FROM TOP, 24 INCHES FROM BOTTOM AND 16 INCHES SPACING BETWEEN.
- C. SANITARY SEWER MAINS
1. ALL SANITARY FORCE MAIN PIPE AND FITTINGS SHALL CONFORM TO ASTM D2241, STANDARD SPECIFICATION FOR POLY VINYL CHLORIDE (PVC) PRESSURE-RATED PIPE, (SDR 21, GREATER THAN 4 INCH DIAMETER).
2. TRACER WIRE SHALL BE INSTALLED WITH ALL SANITARY FORCE MAIN PIPE.
- D. CASING
1. SANITARY SEWERS CONSTRUCTED WITH POLYVINYL CHLORIDE (PVC) AND INSTALLED UNDER RAILROADS SHALL BE GRADED IN CONFORMANCE WITH AASHTO STANDARD C300-89, STANDARD FOR POLYVINYL CHLORIDE (PVC) PRESSURE PIPE, 4 IN. THROUGH 12 IN. FOR WATER DISTRIBUTION, APPENDIX A.
3. APPLICATION
- A. PERMITS AND CODES: THE INTENT OF THIS SECTION OF THE SPECIFICATIONS IS THAT THE CONTRACTOR'S BID ON THE WORK COVERED HEREIN SHALL BE BASED UPON THE DRAWINGS AND SPECIFICATIONS BUT THAT THE WORK SHALL COMPLY WITH ALL APPLICABLE CODES AND REGULATIONS AS AMENDED BY ANY WAIVERS. CONTRACTOR SHALL FURNISH ALL BONDS NECESSARY TO GET PERMITS FOR CUTS AND CONNECTIONS TO EXISTING SEWERS.
- B. THE TERM "LOCAL STANDARDS" AS USED HEREIN MEANS THE STANDARDS OF DESIGN AND CONSTRUCTION OF THE RESPECTIVE MUNICIPAL DEPARTMENT OR UTILITY COMPANY.
- C. EXISTING IMPROVEMENTS: THE CONTRACTOR SHALL MAINTAIN IN OPERATING CONDITION ALL ACTIVE UTILITIES, SEWERS AND OTHER DRAINS ENCOUNTERED IN THE SEWER INSTALLATION. THE CONTRACTOR SHALL REPAIR TO THE SATISFACTION OF THE OWNER ANY DAMAGE TO EXISTING ACTIVE IMPROVEMENTS.
- D. WORKMANSHIP: THIS WORK SHALL CONFORM TO ALL LOCAL, STATE AND NATIONAL CODES AND TO BE APPROVED BY ALL LOCAL AND STATE AGENCIES HAVING JURISDICTION.
- E. TRENCHING: LAY ALL PIPE IN OPEN TRENCHES, EXCEPT WHEN THE LOCAL AUTHORITY GIVES WRITTEN PERMISSION FOR TUNNELING. OPEN THE TRENCH SUFFICIENTLY AHEAD OF PIPE-LAYING TO REVEAL ANY OBSTRUCTIONS. THE MIN. WIDTH OF TRENCH SHALL BE 1.25 TIMES THE OUTSIDE DIA. PLUS 12 INCHES. SHEET AND BRACE TRENCH AS NECESSARY TO PROTECT WORKMEN AND ADJACENT STRUCTURES. ALL TRENCHING TO COMPLY WITH OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION STANDARDS. KEEP TRENCHES FREE FROM WATER WHILE CONSTRUCTION IS IN PROGRESS. UNDER NO CIRCUMSTANCES SHALL PIPE OR APPURTENANCES BE LAID IN STANDING WATER. CONDUCT THE DISCHARGE FROM TRENCH DE-WATERING TO DRAINS OR NATURAL DRAINAGE CHANNELS.
- F. SPECIAL SUPPORTS: WHENEVER, IN THE OPINION OF THE ENGINEER, THE SOIL AT OR BELOW THE PIPE GRADE IS UNSUITABLE FOR SUPPORTING SEWERS AND APPURTENANCES SPECIFIED IN THIS SECTION, SUCH SPECIAL SUPPORT, IN ADDITION TO THOSE SHOWN OR SPECIFIED, SHALL BE PROVIDED AS THE ENGINEER MAY DIRECT, AND THE CONTRACT WILL BE ADJUSTED.
- G. BACKFILLING: BACKFILL SHALL BE PLACED AS SHOWN IN THE PLANS. COMPACT THIS BACKFILL THOROUGHLY, TAKING CARE NOT TO DISTURB THE PIPE. BACKFILL UNDER AND WITHIN 5 FEET OF WALKS, PARKING AREAS, DRIVEWAYS AND STREETS SHALL BE GRANULAR MATERIAL ONLY AND THOROUGHLY COMPACTED BY APPROVED METHODS.
- H. THE FLOW CHANNELS WITHIN MANHOLES SHALL BE AN INTEGRAL PART OF THE PRECAST BASE. THE CHANNELS SHALL BE SHAPED AND FORMED FOR A CLEAN TRANSITION WITH PROPER HYDRAULICS TO ALLOW THE SMOOTH CONVEYANCE OF FLOW THROUGH THE MANHOLE. THE BENCH WALL SHALL BE FORMED TO THE CROWN OF THE INLET AND OUTLET PIPES TO FORM A "U" SHAPED CHANNEL. THE BENCH WALL SHALL SLOPE BACK FROM THE CROWN AT ¼ INCH PER FOOT TO THE MANHOLE WALL.
- I. LEAKAGE TESTING: THE CONTRACTOR SHALL FURNISH THE NECESSARY EQUIPMENT TO TEST SEWERS FOR INFILTRATION. ALL SANITARY SEWER GRAVITY LINES, UPON COMPLETION, SHALL BE REQUIRED TO PASS ONE OF THE FOLLOWING TESTS:
- J. HYDROSTATIC TEST: A HYDROSTATIC TEST SHALL BE PERFORMED WITH A MINIMUM OF TWO (2) FEET OF POSITIVE HEAD. THE RATE OF EXFILTRATION OR INFILTRATION SHALL NOT EXCEED TWO HUNDRED (200) GALLONS PER INCH OF PIPE DIAMETER PER LINEAR MILE PER DAY.
- K. LOW PRESSURE AIR TEST: A LOW PRESSURE AIR TEST SHALL BE CONDUCTED IN ACCORDANCE WITH ASTM F1417, STANDARD TEST METHOD FOR INSTALLATION ACCEPTANCE OF PLASTIC GRAVITY SEWER LINES USING LOW PRESSURE AIR, FOR PLASTIC PIPE.
- L. ALL SANITARY FORCE MAIN LINES, UPON COMPLETION, SHALL BE REQUIRED TO PASS A LEAKAGE TEST CONDUCTED IN ACCORDANCE WITH AWWA STANDARD C905-94, AWWA STANDARD FOR UNDERGROUND INSTALLATION OF POLYVINYL CHLORIDE (PVC) PRESSURE PIPE AND FITTINGS FOR WATER.
- M. ALL SANITARY SEWER MANHOLES SHALL ALSO BE AIR TESTED IN ACCORDANCE WITH ASTM C1244-93, STANDARD TEST METHOD FOR CONCRETE SEWER MANHOLES BY NEGATIVE AIR PRESSURE (VACUUM) TEST.
- N. FLUSHING SEWERS: FLUSH ALL SANITARY SEWERS EXCEPT BUILDING SEWERS WITH WATER TO OBTAIN FREE FLOW THROUGH EACH LINE. REMOVE ALL SILT AND TRASH FROM APPURTENANCES JUST PRIOR TO ACCEPTANCE OF WORK.
- O. PLASTIC SEWER PIPE INSTALLATION: PLASTIC SEWER PIPE SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321 PER LATEST REVISION. PIPES SHALL BE TESTED AFTER THIRTY DAYS, USING A MANDREL THAT IS 95% OF THE INSIDE DIAMETER OF THE PIPE. BEING TESTED. S4D MANDREL SHALL BE PULLED BY HAND THROUGH EACH PIPE SECTION TO ENSURE DEFLECTION IS LESS THAN ACCEPTABLE LIMITS.
- P. STORM WATER CONNECTIONS: NO ROOF DRAINS, FOOTING DRAINS AND/OR SURFACE WATER DRAINS MAY BE CONNECTED TO THE SANITARY SEWER SYSTEMS, INCLUDING TEMPORARY CONNECTIONS DURING CONSTRUCTION.
- Q. WATERLINE CROSSING: WHERE WATER LINES AND SANITARY SEWERS CROSS AND WATER LINES CANNOT BE PLACED ABOVE THE SEWER WITH A MINIMUM OF 18 INCHES VERTICAL CLEARANCE, THE SEWER MUST BE CONSTRUCTED OF WATER WORKS GRADE DUCTILE IRON PIPE WITH MECHANICAL JOINTS WITHIN 10 FEET OF THE WATER LINE.
- R. UTILITIES: IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY ALL EXISTING UTILITIES AND CONDITIONS PERTAINING TO HIS WORK. IT SHALL ALSO BE THE CONTRACTOR'S RESPONSIBILITY TO CONTACT THE OWNERS OF THE VARIOUS UTILITIES BEFORE WORK IS STARTED. THE CONTRACTOR SHALL NOTIFY IN WRITING THE OWNER AND THE ENGINEER OF ANY CHANGES, ERRORS OR OMISSIONS FOUND ON THESE PLANS OR IN THE FIELD BEFORE WORK IS STARTED OR RESUMED.
- S. SERVICE LATERALS: INDIVIDUAL BUILDING LINES SHALL BE 6 INCHES IN DIAMETER AND OF MATERIAL EQUAL TO THAT SPECIFIED IN 2A OF THIS SECTION. SERVICE LINES SHALL BE CONNECTED TO THE MAIN SEWER AT LOCATIONS SHOWN IN THESE PLANS.



SPECIFICATIONS

CG HIGH SCHOOL BLACK BOX THEATER



APPROVED

1/20/2023

NO.	DATE	REVISIONS	BY	APPR.
9				
8				
7				
6				
5				
4				
3				
2				
1				
800				